

## Sensitive Audio Vidéo

*Sensitive Audio Vidéo*

# Conrad Johnson Premier Fourteen Occasion

Prix à l'Unité (pièce): ~~€4 500.00~~ (Taxes 19.6 %  
comprises) **€1 500.00** (Taxes 19.6 % comprises)  
**Remise: €3 000.00**



The Premier Fourteen was the first preamp in the Conrad Johnson Premier product line to offer remote control. The Premier Fourteen introduced Conrad-Johnson's innovative volume control employing a micro-processor to select combinations from an array of metal-foil resistors. This produces a stepped attenuator with 100 steps in approximately .7 dB increments. By controlling the two channels independently, balance can also be adjusted in 0.7 dB steps. Only the highest quality resistors are introduced into the signal path by the level control, resulting in a noticeable improvement in sound quality.

The audio circuit of the Premier Fourteen consists of a single triode amplifier direct coupled to a triode cathode follower. The low output impedance of the cathode follower permits the use of the Premier Fourteen even installations with long, highly capacitive amplifier interconnect cables without attenuation of the high frequency information and without softening transients. A zero feedback circuit ensures temporal accuracy and spatial detail.

The Premier Fourteen was selected by many audiophiles and major magazine reviewers for their own personal use due to its superlative handling of musical transients, its dynamic range, and its very wide frequency response. This is the ultimate complement for any piece of high-end audiophile equipment.

### Features:

Inputs/Outputs - PH/AUX1, TUNER, CD, VIDEO, AUX2, plus two EPL loops for external processing or monitor and recording facilities. One pair of main outputs

### Controls:

Source Selector, EPL toggle, level, & power. Sources and EPLs directly accessible by remote.  
Balance by remote.

4 X 6GK5's Replacement Tube Set RTPR-14)

**Click above for technical info on this product or to purchase a replacement tube kit.**

**Specifications:**

**Gain: 25 dB**

**Phase: Phase Inverting**

**Maximum Output is 20 VRMS**

**Distortion: less than .25% THD or IMD at 1.0 V output**

**Response: bandpass 2Hz to more than 100kHz**

**Line Stage 96 dB below 2.5 volt output**

**Dimensions: 19" X 3 \_" x 15 \_"**

**Weight: 23 lbs.**

[Information du Vendeur](#)

**Avis des Clients:** Il n'y a pas encore de commentaire sur ce produit.

Veuillez vous identifier pour poster un commentaire.